PS760

The High-Definition Multimedia Document Camera



The Lumens™ PS760 is an adaptable high-definition multimedia document camera. With 20x optical zoom and 1080p / UXGA resolution that delivers clear images and crisp text every time, the Lumens™ PS760 is ideal for lecture halls and folds to just 6″(15 cm) height for storage in a podium or cart. The Lumens™ PS760 operates without a computer or with any interactive whiteboard software. Special features include a built-in backlight, support for USB mouse controllers, and stand-alone one-touch audio and video recording and playback. These features and its unlimited 5 year REPLACEMENT warranty, make the Lumens™ PS760 a perfect choice for educators creating a innovative learning environment.

Key Feature

- High Definition, 1080p, UXGA, WXGA, SXGA, and XGA
- 20x optical zoom
- HDMI output
- Up to 30 frames per second live display
- Excellent Color Reproduction
- One-touch video/audio Recording and Playback
- S-video, C-Video input
- Dual VGA inputs and outputs
- Built-in Microphone
- USB drive port reads up to 32 GB thumb drives
- Compatible with all interactive whiteboards
- Time-lapse photography
- Automatic and manual Slideshow
- Full-sized backlight lightbox
- 5-year Full REPLACEMENT Warranty





Specifications

IMAGING

Sensor Technology: CMOS

Output Resolution: XGA (1024 x 768), SXGA (1280 x 1024), WXGA

(1280 x 800), UXGA (1600 x 1200), 1080p

Frame Rate: Up to 30 fps

Zoom Capacity: 20x optical zoom and 5x digital zoom

Capture Area: 18" x 13.5" (457 x 342 mm)

LIGHTING

Lamp Type: Dual LED Lamp Gooseneck

Backlight: LED Backlight 8.3"x 11.7"(210 x 297 mm)

INPUT/OUTPUT

Ethernet: Yes, for IP Address and Remote control Power Supply: External, I2VDC Adapter (100-240VAC)

HDMI Output: Yes

VGA In: 2 ports, active pass through from the computer to an external moni-

tor, can switch VGA source between 2 computers

VGA Out: 2 ports, to projector and to monitor for VGA pass through Audio In: 3 audio in (Built-in microphoe \times 1, Video \times 1, and VGA \times 1)

Audio Out: 3.5mm phone jack for earphones or speakers Internal Memory Capacity: Up to 120 JPEG images External Memory Capacity: USB drive accepts up to 32 GB USB Support: High Speed 2.0 (480 Mbps) Transmission

Video IN : C-Video / S-Video IN x I Video OUT : C-Video / S-Video OUT x I

RS232: I port

SOFTWARE

Podium View[™] Software Included: Support PC Windows 8,7,XP, Vista and

Mac OSX (Free download from Lumens[™] website.)

Video Recording with Audio: Record video with various compression

Playback with audio out- No PC needed

Image Capture: Single or continuous capture of JPEG images

Annotation: Add annotations directly to live image

USB Driver: Support UVC,WIA and TWAIN for integration with interactive white-boards including Promethean $^{\mathbb{N}}$, SMART $^{\mathbb{N}}$, Hitachi Starboard $^{\mathbb{N}}$, Mimio $^{\mathbb{N}}$, and others

SECURITY

Lock-Down Mode: Lock the unit with password entry

Auto Erase Mode: Option to automatically erase internal memory during power

down

Anti-Theft: Kensington Lock Port on document camera chassis

Bolt Holes on Bottom for Mounting : VESA standard 2.95" x 2.95" (75 x 75 mm)

ACCESSORIES

Standard: Power Cord, Power Adapter, VGA cable, USB cable, Audio Cable, Mini-

DIN adapter, Remote, Remote Holer, Microscope adapter, Lens cap

Optional: Padded carrying case, USB 2.0 high speed extension cable - 15 feet (5m)

OPERATION FUNCTIONS

Auto Tune: Yes, single button to adjust for best possible images

Focus: Yes, Auto / Manual Auto Exposure: Yes Auto White Balance: Yes

Photo/Text Mode: Choose photo/grayscale/text mode

Image Mode: Choose normal/35mm slide/microscope/negative film Image Capture: Single or continuous capturing images (time lapse photography) to built-in memory, to an USB flash drive, or to the computer via USB Audio and Video Recording: One touch, standalone audio and video

recording with built-in microphone **Picture in Picture (PIP)**: Yes

Freeze: Yes

 $\textbf{Slide Show:} \ \mathsf{FastSlide}^{\scriptscriptstyle{\mathsf{TM}}} \ \mathsf{Technology} \ \mathsf{to} \ \mathsf{automatically} \ \mathsf{or} \ \mathsf{manually} \ \mathsf{playback} \ \mathsf{saved}$

images

Image Rotation: Full screen image rotation from 90,180 to 270 degree Annotation: Yes, by using Podium View™ software or by UPS or Wireless

Standard Mouse
Spotlight: Yes
Low Light Mode: Yes

Mask: Yes

Pan Across the Screen: Enlarged any part of the image and pan it by using

the arrow keys

Projector Type: Yes, supports both LCD and DLP projectors

Volume control: Yes, via remote or OSD

Matrix switcher: Yes, Can switch VGA/Video Input independently by VGA

OUT(2) setting

Ethernet Image Transfer: Yes, for distance learning Ethernet MIC transfer: Yes, for distance learning Sync. Real Time Clock by Ethernet: Yes Real Time Clock: Yes, record capture time on photo

Key tone: Yes Touch Panel: Yes

OTHER

Weight: 12.3 lbs (5.6 Kg)

Dimensions Operating: 18.3" x 15.2" x 23.1" (466 x 385 x 588 mm)(L x W x H)


Dimensions Folded: 22.3" x 15.2" x 6" (566 x 385 x 152 mm) (L xW x H)

Warranty: 5-year

Compliance: Lumens[™] comply with these important standards: FCC-EMI, cUL,

CE-EMC, CE-LVD, RoHS, and WEEE

I/O CONNECTIONS





Lumens Integration, Inc. 4116 Clipper Court Fremont, CA. 94538 Phone: 888.542.3235

Fremont, CA. 94538 Phone: 888.542.3235 Fax: 510.252.1389 http://www.MyLumens.com Lumens Europe Stationstraat 5 1730 Asse, Belgium Phone: +32 (0) 2 452 76 00 Fax: +32 (0) 2 452 76 00 http://www.MyLumens.com