

TECHNICAL SPECIFICATION



+ Line Transformer + Power Amplifier

■ NC-402 / 402T

| | |
|---------------------------------------|-------------------|
| Rated power | 25W RMS |
| Power [MAX] | 50W |
| Bass speaker | 4" |
| Speakers | 1 tweeter |
| Connections | 2-pole terminal |
| Max SPL | 88dB |
| Impedance | 8Ω |
| Frequency-range | 70Hz ~ 18KHz |
| Dimension [HxWxD] | 243x151x150 mm. |
| NC-402T Line Transformer | 2/4/8/16 W (100V) |

■ NC-502 / 502T / 502A

| | |
|---------------------------------------|-------------------|
| Rated power | 35W RMS |
| Power [MAX] | 75W |
| Bass speaker | 5" |
| Speakers | 1 tweeter |
| Connections | 2-pole terminal |
| Max SPL | 89dB |
| Impedance | 8Ω |
| Frequency-range | 60Hz ~ 18KHz |
| Dimension [HxWxD] | 247x158x152 mm. |
| NC-502T Line Transformer | 2/4/8/16 W (100V) |
| NC-502A Power output | 25W RMS |
| Frequency-range | 20Hz ~ 20KHz |
| Equalization | 2 band EQ +/-15dB |
| Gain | 30dB (max) |

■ NC-602 / 602T

| | |
|---------------------------------------|--------------------|
| Rated power | 50W RMS |
| Power [MAX] | 100W |
| Bass speaker | 6.5" |
| Speakers | 1 tweeter |
| Connections | 2-pole terminal |
| Max SPL | 89dB |
| Impedance | 8Ω |
| Frequency-range | 55Hz ~ 20KHz |
| Dimension [HxWxD] | 348x208x203 mm. |
| NC-602T Line Transformer | 4/8/16/30 W (100V) |

■ NC-802 / 802T

| | |
|---------------------------------------|--------------------|
| Rated power | 85W RMS |
| Power [MAX] | 125W |
| Bass speaker | 8" |
| Speakers | 1 tweeter |
| Connections | 2-pole terminal |
| Max SPL | 90dB |
| Impedance | 8Ω |
| Frequency-range | 45Hz ~ 20KHz |
| Dimension [HxWxD] | 420x255x250 mm. |
| NC-802T Line Transformer | 4/8/16/30 W (100V) |

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897