



# MUSIC

Professional Natural Music Sound.

Music Model. KC

PUBLIC ADDRESS AMPLIFIER  
SOLID STATE -- POWER MIXER



KC- 350W  
KC- 550W  
KC- 750W  
KC-1000W  
KC-1200W

## SPECIFICATION

## POWER MIXER AMPLIFIER

|                          |  |                                     |
|--------------------------|--|-------------------------------------|
| TYPE.....                | MONO POWER MIXER TRANSISTOR  |                                     |
| INPUT.....               | 4 MIC  | IMP. 600 ohm (PHONE JACK)           |
|                          | 2 AUX  | IMP. 47k ohm (PHONE JACK, RCA JACK) |
|                          | 1 TAPE / CD  | IMP. 47k ohm (RCA JACK)             |
| INPUT CONTROL.....       | VOLUME PER CHANNEL   |                                     |
| INPUT TONE CONTROL.....  | LOW -- HIGH +/-16 dB PER CHANNEL   |                                     |
| MASTER CONTROL.....      | MASTER VOLUME CONTROL  |                                     |
| MASTER TONE CONTROL..... | LOW -- MIDDLE -- HIGH +/-16 dB   |                                     |
| MASTER OPTION.....       | MAIN IN (PHONE JACK)   | MAIN OUT (PHONE JACK)               |
|                          | PRE OUT (PHONE JACK)   | RECORD (PHONE JACK)                 |
|                          | ECHO IN (PHONE JACK)   | OUT to ECHO (PHONE JACK)            |
|                          | SEND VOLUME  |                                     |
| INPUT SENSITIVITY.....   | 1 V.RMS AT 1 kHz AT 8 ohm  |                                     |
| S / N RATIO.....         | 100 dB BELOW MAX LEVEL   |                                     |
| FREQUENCY RESPONSE.....  | 50 Hz -- 20k Hz AT +/-3 dB   |                                     |
| THD + NOISE.....         | LESS THAN 0.02% (20 Hz -- 40k Hz AT +10 dBu)   |                                     |
| OPTION.....              | DELAY INPUT WHILE TURN ON<br>BUILT-IN COOLING FAN, AC OUTLET<br>POWER DISPLAY (LINE LED)<br>POWER ON LED |                                     |
| POWER REQUIREMENTS.....  | AC~220 V 50/60 Hz  |                                     |
| OUTPUT.....              | SPEAKER 2 -- 4 ohm, 8 -- 16 ohm<br>LINE MATCHING 70 V, 100 V   |                                     |
| POWER OUTPUT             |  |                                     |
| MODEL                    | POWER  | DIMENSION (W x H x D)               |
| KC- 350W                 | 350 W.RMS  | 483 mm x 143 mm x 500 (460) mm      |
| KC- 550W                 | 550 W.RMS  | 483 mm x 143 mm x 500 (460) mm      |
| KC- 750W                 | 750 W.RMS  | 483 mm x 143 mm x 500 (460) mm      |
| KC-1000W                 | 1000 W.RMS   | 483 mm x 143 mm x 500 (460) mm      |
| KC-1200W                 | 1200 W.RMS   | 483 mm x 143 mm x 500 (460) mm      |