

PMU-SERIES

POWER MIXER with DIGITAL EFFECT & USB INPUT



PMU-SERIES

Stereo Power Mixer 6/8/12 Channel with Digital Effect & USB Input

TECHNICAL SPECIFICATION

- USB / SD card for MP3 input
- Build in 16 DSP effector
- 3 band EQ on all channel input
- 1 Aux send per channel for external effect and monitoring
- 7 band EQ on stereo output
- Dual 10 band level display main output

- PMU-601 : 6 Mono Input + Digital Effect
- PMU-801 : 8 Mono Input + Digital Effect
- PMU-1201 : 12 Mono Input + Digital Effect

| SPECIFICATION : | PMU-601 | PMU-801 | PMU-1201 |
|-----------------------------|----------------------------------|----------------------------------|----------------------------------|
| Input Channel | 6 mono input | 8 mono input | 12 mono input |
| Power Output | 250W x 2 @ 4Ω | 250W x 2 @ 4Ω | 300W x 2 @ 4Ω |
| | 150W x 2 @ 8Ω | 150W x 2 @ 8Ω | 180W x 2 @ 8Ω |
| Frequency Response | 18Hz - 18KHz | 18Hz - 18KHz | 18Hz - 18KHz |
| T.H.D. | 0.005% / 0.004% A-weighted | 0.005% / 0.004% A-weighted | 0.005% / 0.004% A-weighted |
| Signal to Noise Ratio | 110dB / 112dB A-weighted | 110dB / 112dB A-weighted | 110dB / 112dB A-weighted |
| Parametric EQ | | | |
| HIGH | +/-15dB, 12kHz | +/-15dB, 12kHz | +/-15dB, 12kHz |
| MID | +/-15dB, 100Hz~6kHz | +/-15dB, 100Hz~6kHz | +/-15dB, 100Hz~6kHz |
| LOW | +/-15dB, 80Hz | +/-15dB, 80Hz | +/-15dB, 80Hz |
| Dimension [HxWxD] | 130 x 420 x 400 mm. | 130 x 553 x 400 mm. | 130 x 686 x 400 mm. |

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897