

**QTA 4000 SERIES** four-channel power amplifiers

The QTA-4060P, and QTA-4120P range of Power amplifiers have been designed for four channel operation. This is getting even better at saving rack space for those Licensed venue installations where there is nowhere to install a rack. The beauty of these amplifiers is that they are not deep. Only 420mm so no need to purchase those more expensively deep racks.

**features**

- 4 x XLR Inputs
- Rear mounted level controls for each channel
- Rear mounted switch for selection of 100mV or 1v sensitivity for each channel
- 1/4 in jack balanced outputs
- Phoenix connector in/out connections
- Separate 24v operation capability on each channel
- Overload, over temperature and speaker short circuit protection
- 3 year replacement warranty



**QTA-4060P** power amp

- Output Power (RMS): 60W x 4
- Power Supply: Main Voltage: 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: < 1% @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (balanced), 1v @ 10K Ω
- Outputs: 8Ω, 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 160W
- DC Power Consumption: 5A
- Dimensions (mm): 132 (H) x 425 (W) x 420 (D)
- Weight: 21 Kg
- Mounting options: Table top or 19" rack mountable



**QTA-4120P** power amp

- Output Power (RMS): 120W x 4
- Power Supply: Main Voltage: 230V 50/60Hz, Battery Voltage: DC 24V
- Total Harmonic Distortion: < 1% @ 1KHz, rated power
- Sensitivity: XLR, Phone Jack (balanced), 1v @ 10K Ω
- Outputs: 8Ω, 70V, 100V
- Signal to Noise Ratio: 86 dB
- Indicator: Power On, Level
- AC Power Consumption: 320W
- DC Power Consumption: 8A
- Dimensions (mm): 132 (H) x 425 (W) x 420 (D)
- Weight: 25 Kg
- Mounting options: Table top or 19" rack mountable

