

Vivitek D536-3D

XGA projector with built-in 2D to 3D content conversion technology



Product Features

- DLP[®] and BrilliantColor[™] technologies for sharp and detailed image quality
- Integrated 2D to 3D content conversion technology
 - Automatically converts almost any 2D content into 3D ready material for enhanced viewing pleasure
- High-efficiency lamps that last up to 4,000 hours (in economy mode)
- High brightness and contrast ratio
- Built-in enhanced color and display adjustments
- 3D ready for gaming and movies
- Connectivity options including: HDMI V1.3, VGA-Out, RJ45 and RS-232C
- Keypad lock prevents accidental system adjustments
- Great portability at 1.9kg

Product Photos







| Product Specifications | |
|------------------------|--|
| Display Type | DLP |
| Brightness | 3200 Lumens |
| Native Resolution | XGA (1024 x 768) |
| Maximum Resolution | UXGA (1600 x 1200) |
| Contrast Ratio | 3000:1 |
| Lamp Life and Type | 3,000/4000 Hours (Std./Eco. Mode), 240W |
| Throw Ratio | 1.92 - 2.14:1 |
| Image Size (Diagonal) | 40" - 300" |
| Projection Distance | 1 - 10m (3.28ft - 32.8ft) |
| Projection Lens | F = 2.52 - 2.73, f = 24.34 - 25.95mm |
| Zoom Ratio | 1.1x |
| Aspect Ratio | 4:3 Native, 16:9 Compatible |
| Offset | 128% |
| Keystone Correction | Vertical +/- 15° (+/- 30 step) |
| Horizontal Frequency | 15, 30-90KHz |
| Vertical Scan Rate | 43 - 85Hz |
| Speakers | 2W (Mono) |
| Lens Shift Range | N/A |
| Video Compatibility | SDTV (480i, 576i), EDTV (480p), HDTV (720p, 1080i), NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM |
| I/O Connection Ports | HDMI 1.3V, VGA-In, S-Video, Composite Video, Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C |
| Projection Method | Table Top, Ceiling Mount (Front or Rear) |
| Security Solutions | Kensington® Security Slot, Security Bar, Keypad Lock |
| Dimensions (W x D x W) | 261 x 190 x 78mm (10.28" x 7.48" x 3.07") |
| Weight | 1.9kg (4.2lbs) |
| Noise Level | 35dB/29dB (Std. / Eco. Mode) |
| Power Supply | AC 100-240V, 50/60Hz |
| Power Consumption | 230W (Eco. Mode), 300W (Std. Mode), <1W (Standby) |
| Standard Accessories | AC Power Cord, VGA Cable, Carrying Case, Remote Control, Batteries for Remote, Lens Cap, Documentation Kit |
| Optional Accessories | Replacement Lamp, Remote, Carrying Case |

©2011 Vivitek Corporation. Vivitek is a trademark of Vivitek Corporation. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

DLP





