



acmaudio

SRP110

www.acmaudio.com





acmaudio

SRP110



Our SRP compact full range series speaker from 10", 12", 15" to double 15" display all the features expected from a product range with such a distinguished pedigree. Made from high density MDF painted in a hardwearing painted ideally suited for both mobile and fixed installation application. Perfect linear response, big dynamic and low distortion drivers with proprietary custom made voice coil are loaded and accurate crossover design make sure a clear sound available. Additionally, SRP series subwoofer will complement with SRP series full range speaker. All cabinets in SRP series are supplied with 6 strength brackets inside the cabinet and 12xM10 threaded mounting points to accommodate a number of mounting options.

Technical Specification:

Freq. Range (-10dB):	70Hz~20kHz
Freq. Response (-3dB):	85Hz~20kHz
Rec.Hipass Frequency:	50Hz
Axial Sensitivity:	95dB (1W/1m)
Max Calculated SPL:	124dB
Horizontal Coverage:	90°
Vertical Coverage:	80°
Rated System Power:	200W Continuous 800W Peak
LF Transducer:	10"/65mm
HF Transducer:	1"/34mm
Crossover Frequency:	2.5kHz
Nominal Impedance:	8 ohms
Connector:	2xNL4 Speakon
Dim(HxWxD):	300mmx485mmx321mm
Net Weight:	16Kg
Shipping Weight:	17.5Kg

