

PASSIVE

PC-SERIES



TECHNICAL SPECIFICATION

PC-12 / PC-15 : PASSIVE PORTABLE LOUDSPEAKER

PC-12	PC-15
Frequency-response 45Hz ~ 20KHz	Frequency-response 45Hz ~ 20KHz
RMS power handling 250W RMS	RMS power handling 250W RMS
Peak power handling 500W PEAK	Peak power handling 500W PEAK
Nominal impedance 8Ω	Nominal impedance 8Ω
Sensitivity [1w/1m] 96dB	Sensitivity [1w/1m] 98dB
Connections 2 x speakon	Connections 2 x speakon
Low frequency 12" woofer	Low frequency 15" woofer
High frequency 34 mm. titanium driver	High frequency 34 mm. titanium driver
Dimension [HxWxD] 660x390x357 mm.	Dimension [HxWxD] 790x475x420 mm.
Weight 15.5 kg.	Weight 25.5 kg.

<http://www.nts-solution.com>

All features & specifications are subjected to change without notice.



บริษัท เอ็นทีเอส อิเล็กทรอนิกส์ โซลูชั่น จำกัด
NTS Electronic Solution Co., Ltd.

1439-1441 ถนนเจริญนคร แขวงบางลำภูล่าง เขตคลองสาน กรุงเทพฯ 10600

โทรศัพท์: 0-2438-7023-4, 0-2437-7639 โทรสาร: 0-2437-1897

<http://www.nts-solution.com> E-mail: nts@nts-solution.com

1439-1441 Charoennakorn Rd. Banglumpoolang Klongsan Bangkok 10600, Thailand

Tel: (+66-2) 438-7023-4, (+66-2) 437-7639 Fax: (+66-2) 437-1897

