

# SVGA Projector

Light, Bright, and Portable Projector

**PJD5134**



**HDMI®**  
HIGH DEFINITION MULTIMEDIA INTERFACE

The ViewSonic® PJD5134 is a high-performance SVGA 800x600 DLP® projector with 3,000 ANSI lumens and 15,000:1 contrast ratio. This projector is packed with features including HDMI®, DynamicEco™, multiple PC and video input options, 1.1x optical zoom, keystone correction and integrated speaker. With its HDMI input, the PJD5134 can display 3D content directly from a 3D Blu-ray player. Presenters can put the PJD5134 in "standby" mode reducing brightness down to 30% with DynamicEco™ technology when they need to shift audience's focus without restarting the projector. Filter-less design and energy-saving Eco-modes provide for virtually zero maintenance and enhanced product reliability. The PJD5134 portable design is ideal for tabletop use or mounting on a ceiling in both classrooms and corporate offices.

### Bright in Virtually Any Setting

Packed with 3,000 lumens and a high contrast ratio of 15,000:1 (with DynamicEco™), your presentations are guaranteed to be vibrant even in the brightest office environments.

### 3D Blu-ray Ready with HDMI


Equipped with the latest HDMI, ViewSonic's PJD5134 projector can now display 3D images directly from 3D Blu-ray players. The PJD5134 is designed to provide amazing 3D visual experience for classroom, office and even home environments.

### Reliable Picture Quality & Color Performance


ViewSonic DLP projectors provide reliable picture quality you can trust and superior color performance you can count on after thousands of hours of usage. Built on DLP technology, the ViewSonic PJD5134 projector virtually eliminates image degradation known as color decay – yellow/faded tint that LCD projectors may develop after extended use. Even after years of use, the PJD5134 is still producing a stunning, sharp image that lasts.

### Take Control of Audience's Focus

With the DynamicEco button on the remote, take command of presentations by dimming the screen image up to 70%. The projector will also auto activate DynamicEco when the unit is not in use. When DynamicEco is activated, the lamp's power consumption is significantly reduced – a great energy-saving design for low Total Cost of Ownership (TCO).



With DynamicEco™



Without DynamicEco™

# SVGA Projector

**PJD5134**



## BrilliantColor™ Technology

The ViewSonic PJD5134 projector with BrilliantColor technology features multi-color processing to produce stunning, vibrant colors. Unlike other technologies such as LCD which use just 3 primary colors to produce the image, the PJD5134 uses up to 6 separate colors. The sophisticated 6-segment color wheel enhances the yellow color performance that is the key to accurate and vivid color reproduction. With multi-color processing, colors are richer and more vibrant with exquisite and precise detail.



## Maintenance Free

ViewSonic's PJD5134 projector features a filter-less design. Unlike LCD projectors that require the user to clean, sometimes to replace, filters after every 100 to 300 hours of operation, ViewSonic's PJD5134 projector is filter-less, eliminating the need for filter cleaning or filter replacement. This saves you significant maintenance dollars and labor over the projector's lifespan, and lowers your total cost of ownership (TCO)





## Long Lamp Life up to 6000 Hours

The new advanced lamp technology extends the lamp life up to 6000 hours\* and saves on maintenance costs.

Projection Distance		Screen Size (4:3) Diagonal	
Feet	Meters	Inches	Meters
3.6	1.1	30	0.8
9.8	3.0	80	2.0
14.8	4.5	120	3.0
18.7	5.7	150	3.8
24.6	7.5	200	5.1
30.8	9.4	250	6.4
37.1	11.3	300	7.6

## Optional Accessories

Replacement Lamp .....	RLC-078
Wall Mount Kit .....	WMK-005
3D HD Video Processor .....	VP3D1
3D Active Shutter Glasses.....	PGD-250
Wireless Presentation Gateway .....	WPG-series
Soft Case .....	PJ-CASE-001
Extended 5-Year Warranty .....	PRJ-EW-07-02



## Specifications

<b>DISPLAY</b>	Type	0.55" Digital Micromirror Device (DLP™)	
	Resolution	SVGA 800x600 (native)	
	Lens	1.1x Manual optical zoom / manual optical focus	
	Keystone	Vertical digital keystone correction (+/- 40°)	
	Size	24 – 300 in. / 0.6 – 7.6 m (diagonal)	
	Throw Distance	3.3 – 37.0 ft. / 1.0 – 11.3 m	
	Throw Ratio	1.86~2.04:1	
	Lamp	190 watt	
	Lamp Life	4,500/6,000/10,000 hours* (Normal/Eco-mode/DynamicEco™)	
	Brightness	3,000 Lumens	
	Contrast Ratio	15,000:1 (w/ DynamicEco™)	
	Aspect Ratio	4:3 (native)	
	Color Depth	30 bits, 1.07B Color (10+10+10)	
Color Wheel	6-seg RGBCYW / 7200rpm		
<b>INPUT SIGNAL</b>	Computer and Video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SECAM (B, D, G, K, K1, L), SD 480i and 576i, ED 480p and 576p, HD 720p, 1080i, 1080p	
	Frequency	Fh: 31–100KHz, Fv: 48–120Hz	
<b>COMPATIBILITY</b>	PC	VGA to 1600x1200 UXGA	
	Mac®	Up to UXGA (may require MAC adaptor)	
<b>CONNECTOR</b>	RGB Input	15-pin mini D-sub (x2)	
	RGB Output	15-pin mini D-sub	
	Digital Input	HDMI	
	Component Input	15-pin mini D-sub (x2, shared with RGB)	
	Composite Input	RCA jack	
	S-Video Input	4-pin mini-DIN	
	Audio Input	3.5mm mini jack	
	Audio Output	3.5mm mini jack	
<b>AUDIO</b>	Speaker	2W	
	<b>POWER</b>	Voltage	100–240VAC (Auto Switching), 50/60Hz (universal)
		Consumption	250W (typ) / <1W (stand-by mode)

<b>CONTROLS</b>	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
	OSD	Display, Picture, Source, System Setup (Basic), System Setup (Advanced), Information (See user guide for full OSD functionality)
<b>OPERATING CONDITIONS</b>	Temperature	32°F–104°F (0°C–40°C)
	Humidity	10%–90% (non-condensing)
	Altitude	0–6,000 ft (1,800m), operational up to 10,000 ft (3048m)
<b>NOISE LEVEL</b>	Normal / Eco-mode	32dB / 29dB
	<b>DIMENSIONS (W x H x D)</b>	Physical
Packaging		14.2 x 12.8 x 7.4 in. / 360 x 325 x 188 mm
<b>WEIGHT</b>	Net	4.6 lb. / 2.1 kg
	Gross	7.5 lb. / 3.4 kg
<b>REGULATIONS</b>		CB, UL, cUL, FCC (including ICES-003), CE, UL-Argentina, NOM, GS, GOST-R, SASO, Ukraine, PSB, C-Tick, Korean-KC, CCC, CECP, WEEE, RoHS
<b>WARRANTY</b>		3-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service**

## What's in the box?

PJD5134 projector, power cable, VGA cable, remote control with batteries, Quick Start Guide, ViewSonic Wizard DVD (with User Guide).



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

\*Lamp life may vary based on actual usage and other factors. \*\*One year Express Exchange® service requires product registration. Programs, specifications and availability are subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. DLP® and DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Copyright © 2012 ViewSonic Corporation. All rights reserved. [16647-00B-03/13]